

DISTAC WELD

ANTISPATTER SPRAY FOR WELDING

CHARACTERISTICS

Base:	Mixture of synthetic silicone-free anti-spatter agents
Propellant:	Denatured and odourless hydrocarbon (VOC Free) Flammable.
Appearance:	Transparent oil.
Temperature resistance:	Until 250°C
Biodegradability:	More than 85%.
Film Thickness:	2-3 micron
CFC free	
DICHLOROMETHANE free	



APPLICATIONS

DISTAC WELD is a silicone-free anti-spatter spray for metal.

It is used as an anti-spatter with the piece to be welded and as a protector with the welding torch nozzles. Thanks to its composition free of silicone, it allows successive treatments as varnish, galvanization, and chromium plated.

It makes welding easier and faster, avoiding the formation of leaks or cracks.

INSTRUCTIONS OF USE

Shake well before use.

Spray the product around the pieces to be welded at a 25 cm distance.

PACKAGING

Spray Aerosol ml 400/500

Box 25 Aerosol

Product Code 10610/04W and 10610/05W

Revision date 01.08.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet