

Grasso ALTE TEMPERATURE

High temperature infusible grease
Anti-wear, Anti-seize, Anti-corrosion
E.P. (Extreme Pressures)



FEATURES

Grasso ALTE TEMPERATURE CAMP® Professional is a special infusible black-colored grease, enriched with solid lubricant of molybdenum disulfide and anti-seizing compounds, specific for the lubrication of mechanical parts subjected to very high temperatures and high loads. Creates a lubricant film on metal surfaces, with very high adherence, but mostly of a very low friction coefficient - even under high pressure and high temperature.

The lubricant acts in a fluid phase up to 200° C. Above this temperature, the solid lubricant, made up of Molybdenum Bisulfide, it continues to guarantee lubrication and anti-seize protection, as follows: under normal conditions up to 400° C; in oxygen/oxidizing environments, up to 1000 ° C

Grasso ALTE TEMPERATURE CAMP® Professional contains antioxidant, anti-rust and E.P. (Extreme pressures) additives, for complete protection. It has excellent lubricating, anti-sealing and anti-wear properties. Resists oxidation and chemical agents.

APPLICATIONS

Grasso ALTE TEMPERATURE CAMP® Professional is used in different sectors: steel mill, foundry, machining plastics, automotive, engineering, etc. Indicated for exhaust manifolds, joints and crossbows, for assembly and maintenance operations in the automotive field. Recommended for the lubrication of bearings, toothed gears, articulated arms, cables, pins, tracks, buckets, crank mechanisms in general, particularly stressed mechanical parts and/or in the presence of high working temperatures.

PROPERTIES AND ADVANTAGES

- Great resistance to heavy loads and high temperatures
- Reduces friction and protects against oxidation
- Exceptional mechanical stability and strong adhesion
- Excellent resistance to oxidation, moisture and chemicals
- Allows longer maintenance intervals

TECHNICAL DATA

Color:	black
NLGI Consistency:	2/3
Operating temperature:	from -15°C to +200°C
Water resistance:	fair
Wlding loads:	>700 Kgs
Water solubility :	insoluble

Warnings: the information and the advice contained in this datasheet correspond to our most recent technical and applicative knowledge and are supported by ongoing laboratory research. However, before operating the product, anyone who intends to use the product must ensure that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product. Please refer to the current version of the Technical Data Sheet, available from our web site www.campitalia.it



CAMP S.r.l.

Registered Office: C.so Umberto I 103, 70010 Adelfia BA Italy

Headquarters: Via G. Decaro, Zona PIP Lotto 18-19-20, 70016 Noicattaro BA Italy

Tel/fax +39 080 4782768
web www.campitalia.it
e-mail info@campitalia.it

STORAGE

Store in a cool, dry place, in original closed containers.

PACKAGING

Tube 150 ml	Packaging: 12 pcs	Code: 1109 150	Ean: 8056736862513
Pot 1 kg	Packaging: 6 pcs	Code: 1109 001	Ean: 8056736862520

Warnings: the information and the advice contained in this datasheet correspond to our most recent technical and applicative knowledge and are supported by ongoing laboratory research. However, before operating the product, anyone who intends to use the product must ensure that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product. Please refer to the current version of the Technical Data Sheet, available from our web site www.campitalia.it

CAMP S.r.l.

Registered Office: C.so Umberto I 103, 70010 Adelfia BA Italy

Headquarters: Via G. Decaro, Zona PIP Lotto 18-19-20, 70016 Noicattaro BA Italy



Tel/fax +39 080 4782768
web www.campitalia.it
e-mail info@campitalia.it