TECHNICAL DATA SHEET

PENTRIX 100

RED PENETRANT SPRAY

CHARACTERISTICS

Base:Mixture of petrol distillates, dyestuffs and low superficial tension protectorsAspect:Red liquidPropellant:Denatured and odourless hydrocarbon (VOC Free)CFC free

APPLICATIONS

PENTRIX 100 is a red penetrating liquid in spray formulated to discover the cracks or porosity caused by the welding on ferrous materials and others. Thanks to its intense colour and composition, PENTRIX can penetrate into the most difficult parts giving prominence to the welding cracks.

PROPERTIES

- Good Penetrating power
- Low content of chlorine and sulphur

DESCRIPTION

Shake well the can before using it.

Degrease and clean the surface to be treated with the spray degreaser METACLEAN.

Spray PENTRIX 100 on the treated parts, the spray is equipped with a little tube that permits to enter into the most difficult parts reaching in this way any point.

Wait from 10 to 70 minutes for the complete penetration of the product.

Clean the treated surfaces with water or solvents. Do not directly spray the solvent on the treated surfaces, because it could eliminate all the red liquid.

Use RIVELEX 200 to find out the cracks.

The bases used are in compliance with the following rules:

MIL-I-25135E, type II, METHOD A and C, writing at QPL 15

AMS 2644 Inspection Material, Penetrant (Type 2, method A e C, liv. Sens. N/A) writing at QPL 3. DIN 54-152

The content of chlorine and sulfur means as halogens, it is less of the minimum allowed of ASMES laws. 2004 ASME Code, Section V "Nondestructive examination" Article 6 "liquid Penetrate Examination" §T-641 "Control of Contaminants"

HOWMET PM 127A

Manoir Industries Outreau CMS-01 Rev.C du 02/11/1987

Manoir Industries Outreau CMS-02 Rev.C du 13/03/1992

EN ISO 3452-2 "Non Destructive Testing - Penetrate Testing" – "Testing of penetrates Materials-Sensibilitè II" Approved to SAE AMS 2644 Issue E and listed in QPL-AMS2644-4

PACKAGING

Spray Aerosol ml 400 Box 12 Aerosol Product Code 16410/04

Revision date 01.08.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet

Tel: +39 0444 649766 Fax: +39 0444 440018



