

RIVELEX 200

WHITE DETECTOR SPRAY

CHARACTERISTICS

Base:	Mixture of white solvents and powders
Aspect:	White liquid
Propellant:	Denatured and odourless hydrocarbons (VOC Free)
It does not contain CFC	



APPLICATIONS

RIVELEX 200 is a spray that detects the cracks or porosity on welded surfaces.

It allows a fast application, thanks to its rapid evaporation solvents; the product leaves a white powder layer that detects the porosity on welded surface.

It does not damage the treated materials.

It can be used in combination with red and fluorescent penetrants (PENTRIX 100).

Chemical base used for the formulation is compliance with ASME 2644. Type II; MIL-I-25135.form D, type II.

INSTRUCTIONS OF USE

Shake the can before using.

Spray RIVELEX 200 from 20-30 cm distance on the part previously treated with the penetrant liquid (PENTRIX 100).

Wait from 10 to 20 minutes.

Inspect the treated materials.

PACKAGING

Spray Aerosol ml 400

Box 12 Aerosol

Product Code 16510/04

Revision date 02.08.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

© indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet